

KISS 2U V2 PCI 762



HIGH PERFORMANCE COMPUTER PLATFORM FOR CHALLENGING OR NOISE SENSITIVE ENVIRONMENTS

- ▶ low noise < 35 dBa
- ▶ rugged design - shock protected drive bays
- ▶ easy customization with modified standard (MoSt) concept
- ▶ predictable maintenance with remote diagnostic

POSSIBILITIES START HERE



► TECHNICAL INFORMATION

SYSTEM		KISS 2U V2 PCI 762
DIMENSION (H X W X D)		88 x 482 x 472 mm (2U x 19" x 18.58")
WEIGHT		Approx. 8 kg
FRONT I/Os		2x USB 2.0
REAR I/Os		2x GByte LAN, 2x USB 3.0, VGA 2x RS232 on extra Slotbracket
FRONT CONTROLS		ATX Switch
ACCESSIBLE DRIVE BAYS		1x 5.25", 1x 3.5"
INTERNAL DRIVE BAYS		1x 3.5"
POWER SUPPLY		AC 400 W 80+, 100-240 V AC 400 W (80+)
EXPANSION SLOTS		3x PCI 32 Bit, 1x PCI-e x16, 1x PCI-e x4 or 4x PCI-e x4, 1x PCI-e x16
CHIPSET		Q77
CPU BOARD		PCI 762
MEMORY		Upto 16 GByte DDR3
PROCESSOR		i3-3220 3.3 GHz i5-3550S 3.0 GHz i7-3770 3.4 GHz
COOLING		Two hot swappable chassis fans, air filter
TEMPERATURE	NON-OPERATING OPERATING	-20 °C to +70 °C (-4 °F - 154 °F) 0 °C to +50 °C (32 °F - 122 °F)
HUMIDITY	OPERATING/NON OPERATING	10-95 % relative humidity at 40 °C non condensing
SHOCK	OPERATING	15g, 11ms
VIBRATION	OPERATING	10-500 Hz, 1g
NOISE		< 35 dBA
APPROVALS		CE
PROTECTION CLASS		IP 20 optional IP 52
OPTIONS		DVD RW, KISS DA135, KISS DA425, KISS StorSlim, PCCM, Slide rails

► ORDERING INFORMATION

RECOMMENDED CONFIGURATION	DESCRIPTION	MATERIAL NUMBER
KISS 2U V2 PCI762	KISS 2U PCI762, Intel® i7-3770, 16 GB DDR, SATA 1 TB, AC PSU 400 W, 2x PCIe, 3x PCI, 5,25" DVD/RW, Windows 7 Ultimate 64 bit	2-A0JA-2004
KISS 2U V2 PCI762	KISS 2U PCI762, Intel® i5-3550S, 16 GB DDR, SATA 1 TB, AC PSU 400 W, 2x PCIe, 3x PCI, 5,25" DVD/RW, Windows 7 Ultimate 64 bit	2-A0JA-2005
KISS 2U V2 PCI762	KISS 2U PCI762, Intel® i3-3220, 8 GB DDR, SATA 1 TB, AC PSU 400 W, 2x PCIe, 3x PCI, 5,25" DVD/RW, Windows 7 Ultimate 64 bit	2-A0JA-2006
BAREBONE KISS 2U V2 PCI762	KISS 2U PCI762, AC PSU 400 W, 2x PCIe, 3x PCI, CPU Cooler	2-A0JA-0005

► CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: +49 821 4086 0
Fax: +49 821 4086 111
info@kontron.com

NORTH AMERICA

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn